

⊕ What Size French Cleat Do I Need?

Once you know the total weight of your piece, use this chart to select the right cleat(s).

8611 - Cleat, Large, 12" (304 mm)	
Weight Limit	9.75 lbs. (4.42 kg) per cleat with 50% glue
Glue Surface Area	12" x 1.625" (304 x 41 mm)
Thickness	0.25" (6 mm)
Lift off Clearance	0.8125" (21 mm)
Mounting Channel	1" wide x 0.25" (25 x 6 mm) deep
Material	6063 high strength aluminum
Assembled Footprint	12" x 4"

8614 - Cleat, Small, 12" (304 mm)	
Weight Limit	4.5 lbs. (2.04 kg) per cleat with 50% glue
Glue Surface Area	12" x 0.75" (304 x 19 mm)
Thickness	0.1875" (5 mm)
Lift off Clearance	0.5" (13 mm)
Mounting Channel	0.5" (13 mm)
Material	6005A high strength aluminum
Assembled Footprint	12" x 1.9375"

8612 - Cleat, Medium, 12" (304 mm)	
Weight Limit	6 lbs. (2.72 kg) per cleat with 50% glue
Glue Surface Area	12" x 1" (304 x 25 mm)
Thickness	0.25" (6 mm)
Lift off Clearance	0.4375" (11 mm)
Mounting Channel	0.5625" (14 mm)
Material	6063 high strength aluminum
Assembled Footprint	12" x 2.625"

8615 - Cleat, Small, 6" (152 mm)	
Weight Limit	2.25 lbs. (1 kg) per cleat with 50% glue
Glue Surface Area	6" x 0.75" (152 x 19 mm)
Thickness	0.1875" (5 mm)
Lift off Clearance	0.5" (13 mm)
Mounting Channel	0.5" (13 mm)
Material	6005A high strength aluminum
Assembled Footprint	6" x 1.9375"

8613 - Cleat, Medium, 6" (152 mm)	
Weight Limit	3 lbs. (1.36 kg) per cleat with 50% glue
Glue Surface Area	6" x 1" (152 x 25 mm)
Thickness	0.25" (6 mm)
Lift off Clearance	0.4375" (11 mm)
Mounting Channel	0.5625" (14 mm)
Material	6063 high strength aluminum
Assembled Footprint	6" x 2.625"

8616 - Cleat, Small, 3" (76 mm)	
Weight Limit	1.1 lbs. (0.5 kg) per cleat with 50% glue
Glue Surface Area	3" x 0.75" (76 x 19 mm)
Thickness	0.1875" (5 mm)
Lift off Clearance	0.5" (13 mm)
Mounting Channel	0.5" (13 mm)
Material	6005A high strength aluminum
Assembled Footprint	3" x 1.9375"